

FV-PRO AH7553AM-IR 5 Megapixel 3.3-12mm External Vandal Dome Camera - Available March 2018!!



Quick Overview

5 MPX 1500TVL Vandal Dome Camera. 3.3~12mm Varifocal Lens with ICR for True Day / Night auto switch function. 3D DNR. Defog. D-WDR. 30 IR LED's for 30m night vision + Smart IR and Mirror

Details

1080P 2 MPX 1000TVL Vandal Dome Camera. 3.3~12mm Varifocal Lens with ICR for True Day / Night auto switch function. 3D DNR. Defog. D-WDR. 30 IR LED's for 30m night vision + Smart IR and Mirror Image. Motion Detection. 12V DC..

Additional Information

Model	FV-PRO AH7553AM-IR 5 Megapixel 3.3-12mm External Vandal Dome Camera
Call For Price	Yes
Accessories Available	Yes
AES	Yes
AGC	Auto
AGC/Digital Sense up	-
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	-
Connection Cable	DC
Control Capability	-
Dimensions	Width - 114mm - Height - 150mm
DNR	3D

Dual Streaming	Yes
Effective Pixel	2592 x 1944
Enhancement	-
Gamma Correction	0.45
Horizontal Resolution	1000TVL
Image Sensor (CCD)	2+ Megapixel
Joystick Control	-
LCD Screen	-
Lens	2.8~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens Facilities	-
Lens Mount	-
Lens (Optical)	2.8~12mm
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	0 Lux with IR LED's on + Smart IR
Multiple Preset Sequencing	-
POE	-
Power Consumption	-
Power Source	12V DC Regulated
Presets	-
Privacy	-
RS485 Interface	-
Scanning System	PAL
Shutter	1/50s~1/50000s
S/N Ratio	>52db +
Sync. Type	Internal
Sync System	2:1 Internal
Video output	BNC
Video Output Signal	1.0vp-p, 75 ohm composite
Weight(Cameras)	900g
Within Range of IR LEDs	25m