

H265 FV-PRO 3332H2 Pentaplex 32ch non-POE NVR

Quick Overview

The H265 3332H1 is a standard 32CH NVR, which adopts the most advanced SOC technique to ensure High Definition recording in each channel. This NVR will support 4 IP Cameras with simultaneous 4CH playback, and HDMI high resolution display up to 4K.



Details

New 32ch H265 NVR records 60% more than H264 on same size Hard Drive and can also output 4K as well as other HDMI protocols. Supports IP Cameras up to 5 Megapixel @ 25fps. Intuitive and user-friendly Graphic User Interface(GUI), Windows style, operation by Mouse Remote control via IE or CMS: Preview, Playback and Backup. Multi-Mode Recording: Manual, Timer, Motion or Sensor Simultaneous 4CH Playback: Search: Time / Calendar / Events (alarm, motion) . Express and flexible backup via USB or Network. Pentaplex for Live, Record, Playback, Backup and Remote operation. P2P through Cloud Server or standard DHCP, DDNS, PPPoE Network protocol, IE browser and CMS. Dual Stream Technology to Encode Recording Stream and Network Stream respectively. User can adjust Network Stream to fit bandwidth without changing recording quality. Multi-users can be set to be online simultaneously with different passwords. HDMI up to 4K output. Powerful smart phone surveillance supporting Android phone, iPhone. Compatible with 3G Complete SDK function, easy to integrate with other applications Edit audio and video functions like masking objects (hiding objects), choosing day and time from recorded events, adding legends, choosing audio and video quality (128K~2Mbps, Frames per Second, Brightness, Colour, etc.), Cut files to choose special events “ Audio and Video.

Additional Information

Model	H265 FV-PRO 3332H2 Pentaplex 32ch non-POE NVR
Call For Price	Yes
Accessories Included	IR Remote + Mouse
Accessories Optional	-
Alarm Inputs / Relay Outputs	-
Alarm Notification	Yes
Alarm Recording	Yes through camera
Audio Inputs	32 from Cameras
Audio Input Output	-
Backup Device	USB
Call Monitor Output	-

Camera Input	32
Camera Loop Out	-
Compression Method	H265 (optimised)
Device Expansion	-
Dimensions	430(W) x 55(H) x 295(D) mm
Dual Streaming	No
Event Backup	USB
Event List	Yes
Hard Drive Options	1TB / 2TB / 3TB / 4TB / 6TB / 8TB / 9TB / 12TB
Image Record Rate	Up to 800 PPS
Image Quality	Multi options of Picture KB size.
Network Access (LAN)	Yes
Main Monitor Output	1 HDMI / VGA
Mono / Colour	Auto Sense
Motion Detection	Yes
Net Weight	3.8kg
Password Control	Yes
Playback Speed	-
POE	-
Power	AC100~240V
Dome & PTZ Controls	RS485
Record Facilities	24hr / Schedule / Motion
Record Frame Rate (PPS)	Up to 800 FPS
Recording Modes	-
Recording Resolution (Quality Settings)	Multiple
Relay Outputs	1
Remote Interface	-
Resolution (Best)	up to 4K dependant on Monitor and Camera
Tillscan	Option
Time and Date	Yes
Storage Media & Capacity	Hard Drives up to 12TB
Transmission / Networking	Webserver

VGA Monitor Output	1
Zoom	x 10 with Mouse Wheel