

FV-PRO 9554E2 H265 5 Megapixel IP Mini Eyeball with IR LED, WDR 3.6mm Wide Angle lens, Multi Stream, POE



Quick Overview

H265 5MP Real Time Encoding. Multi Stream Mini Dome. 2.8mm Wide Angle Lens. IR LED for 15m night view. 3D & 2D Noise Reduction. WDR. Triple Stream Mic input 12V DC or POE

Details

H265 5MP Real Time Encoding. Multi Stream Mini Dome. 3.6mm Wide Angle Lens. IR LED for 15m night view. 3D & 2D Noise Reduction. WDR. Triple Stream Mic input 12V DC or POE.

Additional Information

Model	FV-PRO 9554E2 H265 5MP IP Indoor / Outdoor Mini Dome with WDR IR LED and POE.
Call For Price	Yes
Accessories Available	Yes
AES	Yes
AGC	Auto
AGC/Digital Sense up	Auto
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	WDR
BLC/SSDR (WDR)	WDR - 120db
Communication System	IP
Connection Cable	DC + POE
Control Capability	-
Dimensions	Base Width 108mm - Height - 87mm
DNR	3D

Dual Streaming	Yes
Effective Pixel	2658(H) x 11944(W)
Enhancement	-
Gamma Correction	0.45
Horizontal Resolution	1500TVL
Image Sensor (CCD)	5 Megapixel
Joystick Control	-
LCD Screen	-
Lens	2.8mm Megapixel Lens
Lens (Digital)	-
Lens Facilities	-
Lens Mount	M12
Lens (Optical)	2.8mm
Minimum Illumination - Colour	0.05 Lux
Minimum Illumination - Mono	0 Lux under IR illumination
Multiple Preset Sequencing	-
POE	Yes
Power Consumption	<2W
Power Source	12V DC Regulated or POE
Presets	-
Privacy	-
RS485 Interface	No
Scanning System	PAL
Shutter	Auto
S/N Ratio	55db +
Sync. Type	Internal
Sync System	2:1 Internal
Video output	-
Video Output Signal	1.0vp-p, 75 ohm composite
Weight(Cameras)	427g
Within Range of IR LEDs	15m