

FV-PRO 9583E2 H265 8 Megapixel Motorised Zoom 3.3-12mm External Vandal Resistant Dome - Available Feb 2018!!



Quick Overview

8MP Variable Real Time Encoding. Dual Stream Vandal Style. ICR auto switch for Day/Night functions. 30 IR LED's for 30m + night vision. Audio. 12V DC or POE..

Details

8 Megapixel High Tier H265 with H264 and MJPEG compatible 3 streams.. Variable Real Time Encoding. Vandal Style. True WDR. ICR auto switch for Day/Night functions. 30 IR LED's for 30m night vision. One Way Audio. 12V DC or POE.

Additional Information

Model	8 Megapixel - 3.3~12mm Motorised lens, True WDR True Day Night, Vandal Resistant, Audio, Triple Stream 12V DC or POE.
Call For Price	No
Accessories Available	Yes
AES	-
AGC	Auto
AGC/Digital Sense up	-
Aperture Correction	H aperture V aperture
Auto Flip	-
BLC	WDR
BLC/SSDR (WDR)	True WDR
Communication System	IP
Connection Cable	DC + POE / Video (RJ45) & (BNC), Audio in / out
Control Capability	-
Dimensions	Width - 150mm - Height - 114mm
DNR	3D

Dual Streaming	Yes + Triple Streaming
Effective Pixel	3840 Ã— 2160
Enhancement	-
Gamma Correction	0.45
Horizontal Resolution	3840 Ã— 2160
Image Sensor (CCD)	8 Megapixel
Joystick Control	-
LCD Screen	-
Lens	3.3~12mm Megapixel Day / Night Lens
Lens (Digital)	-
Lens Facilities	Motorised Zoom
Lens Mount	-
Lens (Optical)	3.3~10mm
Minimum Illumination - Colour	0.1 Lux
Minimum Illumination - Mono	0 Lux with IR LED's on
Multiple Preset Sequencing	-
POE	Yes
Power Consumption	2.5W or 5W with IR on
Power Source	12V DC Regulated or POE
Presets	-
Privacy	-
RS485 Interface	-
Scanning System	PAL
Shutter	Auto
S/N Ratio	52db +
Sync. Type	Internal
Sync System	2:1 Internal
Video output	IP + Composite
Video Output Signal	1.0vp-p, 75 ohm composite
Weight(Cameras)	1kg
Within Range of IR LEDs	30m