

## FV-PRO AH7524AM-IR 1080p 2 Megapixel 2.8 Eyeball Dome Style Camera with IR in White



### Quick Overview

1080P 2 MPX 1000TVL Eyeball Style Dome with ICR for auto switch Day/Night functions. 3D DNR. 25m night vision. 12V DC..

### Details

1080P 2 MPX 1000TVL Eyeball Style Dome with ICR for auto switch Day/Night functions. 3D DNR. 36 IR LED's for 25m night vision. 12V DC..

### Additional Information

<b>Model</b>	FV-PRO AH7524AM-IR 1080p 2 Megapixel 2.8mm Eyeball Dome Style Camera with IR in White
<b>Call For Price</b>	Yes
<b>Accessories Available</b>	Yes
<b>AES</b>	Yes
<b>AGC</b>	Auto
<b>AGC/Digital Sense up</b>	-
<b>Aperture Correction</b>	H aperture V aperture
<b>Auto Flip</b>	-
<b>BLC</b>	Yes
<b>BLC/SSDR (WDR)</b>	Digital WDR
<b>Communication System</b>	-
<b>Connection Cable</b>	DC
<b>Control Capability</b>	-
<b>Dimensions</b>	Width - 109mm - Height - 130mm
<b>DNR</b>	3D

<b>Dual Streaming</b>	Yes
<b>Effective Pixel</b>	1920(H) x 1080(V)
<b>Enhancement</b>	-
<b>Gamma Correction</b>	0.45
<b>Horizontal Resolution</b>	1000TVL
<b>Image Sensor (CCD)</b>	2+ Megapixel
<b>Joystick Control</b>	-
<b>LCD Screen</b>	-
<b>Lens</b>	3.6mm Megapixel Day / Night Lens
<b>Lens (Digital)</b>	-
<b>Lens Facilities</b>	-
<b>Lens Mount</b>	-
<b>Lens (Optical)</b>	3.6mm
<b>Minimum Illumination - Colour</b>	0.1 Lux
<b>Minimum Illumination - Mono</b>	0 Lux with IR LED's on + Smart IR
<b>Multiple Preset Sequencing</b>	-
<b>POE</b>	-
<b>Power Consumption</b>	-
<b>Power Source</b>	12V DC Regulated
<b>Presets</b>	-
<b>Privacy</b>	-
<b>RS485 Interface</b>	-
<b>Scanning System</b>	PAL
<b>Shutter</b>	1/50s~1/50000s
<b>S/N Ratio</b>	>52db +
<b>Sync. Type</b>	Internal
<b>Sync System</b>	2:1 Internal
<b>Video output</b>	BNC
<b>Video Output Signal</b>	1.0vp-p, 75 ohm composite
<b>Weight(Cameras)</b>	500g
<b>Within Range of IR LEDs</b>	25m